

CRYOMECH**Cryocooler Specification Sheet****AL230 with CPA2850**Cold head

Certified cooling capacity at 60 Hz*

Reference operating range

*reduced capacity at 50 Hz

Lowest temperature

Cool down time

Weight

Dimensions

Helium compressor package

Water cooled:

Weight

Dimensions

Electrical rating

Power consumption at steady state

Cooling water flow rate

Air cooled:

Weight

Dimensions

Electrical rating

Power consumption at steady state

Flexible lines

Standard length

Weight per pair

System parameters

Helium pressure

Ambient temperature range

Maximum sound level

Water cooled

Air cooled

AL230

60 W at 30 K

25 W at 20 K 90 W at 40 K 115 W at 50 K

≤17 K with no load

<1 hour to bottom temperature

37 lb (17 kg)

See cold head outline drawing

CPA2850, available as water or air cooled

243 lb (110 kg)

See compressor package outline drawing

200/230 VAC, 3 Ph, 60 Hz

440/480 VAC, 3 Ph, 60 Hz

200 VAC, 3 Ph, 50 Hz

380/415 VAC, 3 Ph, 50 Hz

5.5 kW, 60Hz

4.5 kW, 50Hz

Minimum flow 1.8 GPM (6.8 LPM) at 80 °F (27 °C)
maximum temperature

384 lb (174 kg)

See compressor package outline drawing

200/230 VAC, 3 Ph, 60 Hz

440/480 VAC, 3 Ph, 60 Hz

200 VAC, 3 Ph, 50 Hz

380/415 VAC, 3 Ph, 50 Hz

6.1 kW, 60Hz

5.1 kW, 50Hz

10 ft (3 m)

15 lb (6.8 kg)

210 ± 5 psig (14.5 ± .34 bar) at 60 Hz

220 ± 5 psig (15.2 ± .34 bar) at 50 Hz

45 °F to 100 °F (7 °C to 38 °C)

70 dBA at 1 meter

76 dBA at 1 meter