

CRYOMECH

Helium Reliquefier Specification Sheet

HeRL10 with CPA289C

Reliquefaction rate (Recondensing boil-off from Cryostat)	≥ 18 L/day at 0.50 psig
Cool down time	< 2 hours between start up and liquid helium production
Max operating pressure	5.0 psig (0.34 bar) Pressure relief valve cracking pressure
Cryostat interface	
Standard drain leg diameters:	Ø 1/2 inch (12.7 mm) Ø 3/8 inch (9.5 mm) Ø 12 mm (0.472 inch) (Custom sizes available upon request)
Standard drain leg length	12 inch (305 mm) – 35 inch (889 mm) (Custom lengths available upon request)
Vapor return line	Connects to vent port Supplied with 1/4 inch MNPT and KF16 adaptor
System monitoring and control	
Pressure control	Balances boil-off rate with condensing rate
Temperature monitor	Monitors the cold head temperature using a calibrated diode.
Reliquefier weight	69 lb (31.3 kg)
Cold head	PT410
Helium compressor package	CPA289C, available as water cooled only
Weight	295 lb (134 kg)
Dimensions	See compressor package outline drawing
Electrical rating	200/230VAC, 3 Ph, 60 Hz 460VAC, 3 Ph, 60 Hz 200/220 VAC, 3 Ph, 50 Hz 380/420VAC, 3 Ph, 50 Hz
Power consumption at steady state	8.4 kW, 60 Hz 7.8 kW, 50 Hz
Cooling water flow rate	Minimum flow 3 GPM (11.5 LPM) at 80 °F (27 °C) maximum temperature
Flexible lines	90° elbows at Reliquefier end
Standard length	66 ft (20.1 m)
Weight per pair	120 lb (54.4 kg)
System parameters	
Helium pressure	220 ± 5 psig (15.2 ± .34 bar) at 60 Hz 250 ± 5 psig (17.2 ± .34 bar) at 50 Hz
Ambient temperature range	45 °F to 100 °F (7 °C to 38 °C)
Maximum sound level	70 dBA at 1 meter
Mounting interface	(8) 5/16 -18 threaded holes on HeRL base See Reliquefier outline drawing



Helium Reliquefier Specification Sheet

HeRL10 with CPA289C

Optional Equipment

Reliquefier Stand

Weight (with empty ballast tank) 125 lb (57 kg)

Dimensions - L x W x H 36 inch x 32 inch x 96 inch (92 cm x 81 cm x 244 cm)
(Custom heights available upon request)

Counterweight (liquid volume) 30 gal (114 L)